




TECTUM ROOF DECK OVER WOOD



TECTUM III, E, AND NS DECKS
USE TRUFAST SCREWS OR
DEKFAST
#14 SCREWS WITH 1½" WASHER.
MINIMUM LENGTH IS ONE INCH
LONGER
THAN PANEL THICKNESS.
1½" PENETRATION PREFERRED.



TECTUM I DECK USES DEKFAST
#14 SCREWS WITH 2" WASHER.
MINIMUM LENGTH IS ONE INCH LONGER
THAN PANEL THICKNESS.
1½" PENETRATION PREFERRED.



ONE ROW OF SCREWS IS
REQUIRED AT INTERMEDIATE
SUPPORT.

NOTE: A 3/8" BEAD OF CONSTRUCTION ADHESIVE IS
REQUIRED WHEN SPECIFIED.

1 DECK SCREWED TO WOOD
Scale: N.T.S.

These drawings show typical conditions in which the Armstrong product depicted is installed. They are not a substitute for an architect's or engineer's plan and do not reflect the unique requirements of local building codes, laws, statutes, ordinances, rules and regulations (Legal Requirements) that may be applicable for a particular installation. Armstrong does not warrant, and assumes no liability for the accuracy or completeness of the drawings for a particular installation or their fitness for a particular purpose. The user is advised to consult with a duly licensed architect or engineer in the particular locale of the installation to assure compliance with all Legal Requirements. Armstrong is not licensed to provide professional architecture or engineering design services.

PROJECT NAME: DECK SCREWED TO WOOD					
DATE: 10-16-17	SCALE: N.T.S.	PROJECT NO.: XXX			
REV:	DATE:	DESC.: 2006 - DECK SCREWED TO WOOD			SK1 1 OF 1
REV:	DATE:				