


CUT 1/4" KERF AT JOINTS TO DEPTH 1" ABOVE DOW / TECTUM LAMINATION LINE.



DO NOT USE SILICONE BASED CAULK. USE A HIGH QUALITY LATEX CAULK. USE A LOW RISE SPRAY FOAM. COMPLETELY FILL OPENING FROM BOTTOM TO TOP.

1 TECTUM POOL KERFED JOINT REPAIR
Scale: N.T.S.

These drawings show typical conditions in which the Armstrong product depicted is installed. They are not a substitute for an architect's or engineer's plan and do not reflect the unique requirements of local building codes, laws, statutes, ordinances, rules and regulations (Legal Requirements) that may be applicable for a particular installation. Armstrong does not warrant, and assumes no liability for the accuracy or completeness of the drawings for a particular installation or their fitness for a particular purpose. The user is advised to consult with a duly licensed architect or engineer in the particular locale of the installation to assure compliance with all Legal Requirements. Armstrong is not licensed to provide professional architecture or engineering design services.

PROJECT NAME: TECTUM POOL KERFED JOINT REPAIR					
DATE: 10-30-17	SCALE: N.T.S.	PROJECT NO.: XXX			
REV:	DATE:	DESC.: 2068 - TECTUM POOL KERFED JOINT REPAIR			SK1 1 OF 1
REV:	DATE:				